



Part Number: 5416

5416 thin client *Value Class Thin Client*

The 5416 is an affordable, energy efficient, compact thin client. This unit weighs just over 1lb. allowing flexible mounting options and low shipping costs. The 5416 has no moving parts and consumes only 8-9 watts of energy.



**Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients**

| | |
|---|---|
| ✓ XPe Operating System | ✓ Centralised Management |
| ✓ Small Form Factor for Space-Saving | ✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 and Cisco Compliant |
| ✓ Multiple Level Lock Down Feature with Protected File System | ✓ Wide Screen Support |
| ✓ IE6 (**IE7/8 upon request) | ✓ 1600 X1200 Maximum Resolution |
| ✓ Supports RDP, ICA and VDI Deployment | ✓ Built-in Kensington Security Lock |
| ✓ Energy Efficient (Only 8-9W) | ✓ RoHS and Energy Star Compliant |
| ✓ BlueZone Desktop Terminal Emulation | ✓ VESA Mounting Capability |





System

| | |
|----------------------------|---|
| Operating System | XPe SP2 (Windows Embedded Standard 2009 available upon request) |
| Form Factor | Compact case |
| Management | 10ZiG Management Software |
| Processor | VIA 500MHz |
| Browser | IE6 (**7 or 8 available upon request) |
| Video Resolution | Up to 1600 x 1200 x 32 bit color |
| Wide Screen Support | ● |

Memory

| | |
|----------------------------|-----------|
| RAM (Stand/MAX) | 512MB/1GB |
| Storage (Stand/MAX) | 512MB/8GB |

Software Configuration

| | |
|------------------------|---|
| Host Access | Supports TN5250e/TN3270e, SSL, IBM 3151, (BlueZone Desktop) VT100 and VT200, SCOANSI and others* |
| ICA | Version 12.1 with HDX |
| RDP | 6.1 |
| Client Software | <ul style="list-style-type: none"> Adobe Acrobat Viewer Adobe Flash Player MS Office Viewers Microsoft Outlook Express Windows Media Player Shockwave Sun JVM & MS Java VNC Shadowing |
| VDI Clients | Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer |

Dimensions

| | |
|---------------|--|
| Device | 1.4" W x 6.1" H x 4.8" D 36mm x 156 mm x 122 mm |
| Weight | 1.7 lbs. (0.75kg) |

Audio

| | |
|------------------------|------------------------------------|
| Mic In/Line Out | ● |
| Speaker | x 1 (built in 1W internal Speaker) |

Management

| | |
|---|---|
| 10ZiG Remote Manager | ● |
| Various Client Configurations | ● |
| Shadow Terminals | ● |
| Status Indication | ● |
| Power on, Log off, Reboot and Shut down | ● |
| Task Scheduler | ● |
| Cloning of Terminals | ● |
| Group Operations | ● |
| Update of Firmware | ● |
| Recover Image | ● |
| Configuration of Various Connection Types including 5250 | ● |

Ports

| | | |
|------------------|---------------|----|
| USB Ports | Type 2 | x4 |
| PS2 Port | | ● |

Environmental

| | |
|------------------------------|--------------------------|
| Operating Temperature | 0° ~ 35°C 32° ~ 95°F |
| Operating Humidity | 20% ~ 80% non condensing |

Power

| | |
|----------------------|-------------------|
| Consumption | 8 9 watts average |
| AC/DC Adapter | Included |

Networking

| | |
|--|---|
| | Autosensing, 10/100 Ethernet, RJ 45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option |
|--|---|

Compliance

| | |
|--|-----------------------|
| | RoHS |
| | WEEE |
| | CE |
| | FCC |
| | Energy Star Compliant |

Features

| | |
|--------------------------|---|
| Security Features | <ul style="list-style-type: none"> Kensington Security Lock Slot Auto start/auto restart connection, Multiple level lock down user interface Administrative and user passwords |
| Language Support | US, UK English, German, French, Swedish and others by request |

Ordering Information

| PID | Description |
|---------------|---|
| 5416NE | RBT 416, XPe, IE6 SP2, Sun JVM & MS Java, RDP, ICA, Shockwave, Flash Player, Optical Mouse, Adobe Acrobat Viewer, MS Office Viewers, MS Outlook Express and Windows Media Player. |
| 5416 | Featured software from 5416NE plus BlueZone Desktop Emulation |
| 9001 | USB to Centronics |
| 9004 | VESA Mounting Bracket (with short VGA cable) |
| 9010 | Internal Wireless (802.11 b/g/n + Cisco) |
| 8122b | 122 Key Driverless PC Keyboard |
| 8104b | 104 Key PC Keyboard |

| | |
|----------------------------|---------------------------------|
| ** Requires 1GB DOM | IE 7, Sun JVM 1.6, Adobe 8 or 9 |
|----------------------------|---------------------------------|

*VT320, VT420, VT52, WYSE60, WYSE60/AIF, VAX/AIX, LINUX, HP70094/8, HP70092/6, HP2392A

